



REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2019/07/30	CYF

Detailed Product Description:
 Waterproof connector rating is IP67
 They can not be used permanently under water
 Per ISO-20653,IEC60529

Mechanical characteristics: mating / cycle >100cycles
 Operating temperature: -25°C ~ +85°C

ALL MATERIALS ARE RoHS COMPLIANT



TERMINATION:Solder

Electrical character

Part Number	Contacts	Rated voltage		Rated current	Contact Resistance	Cable OD (mm)
		A/C	D/C			
080103-01-002		50V	60V	3A	10mΩ	3~5.5
080104-01-002		50V	60V	3A	10mΩ	3~5.5
080205-01-001		30V	30V	3A	10mΩ	3~5.5
080106-01-001		30V	30V	1.5A	10mΩ	3~5.5
080108-01-001		30V	30V	1.5A	10mΩ	3~5.5



Shen Zhen Signal Electronics co.,Ltd

DRAWN BY

DATE

CHECKED BY

DATE

APPROVED BY

DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY.
 ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE M8 MALE CONNECTOR WITH SHIELD

SGN NO SEE TABLE

REV.

DWG NO

CUSTOMER


S0

TOLERANCES ARE:

DECIMALES

ANGLES

THIRD ANGLE PROJECTION



.x ±0.5

x.* ±2.0°

SIZE: A4

UNITS: mm

.xx ±0.20

.x.* ±1.0°

SCALE:

SHEET: 1 OF 1