

说明:


额定电压: 见附表
绝缘电阻: > 100MΩ
额定电流: 见附表
连接器的接触电阻≤10mΩ
插拔/周期 >100 cycle
防护等级: IP67
操作温度: -25° C ~ + 125° C
接线OD: 8~10mm

测试条件


导通阻抗: 0.5Ω MAX
绝缘阻抗: 10MΩ MIN
电 压: DC 5KV/0.1S

注: 1. 6芯 (5+PE) 即为8芯 (7+PE) 闭合PIN2和PIN5


2. 端子④单独包装。



LEFT VIEW



SGN NO	ITEM	PART NO.	SPECIFICATION	Q' TY	电压/V AC/DC	电流/A	LEFT VIEW/1:2
170004-01-001	④	YDTE1144	M17 铆铜镀金压接式公端子 Ø2.0×20.1mm	4	630	25	
	②	YDCN0975	M17 4P 公头金属装配式尼龙后胶芯 L=14.5mm	1			
	①	YDCN0976	M17 4P 公头金属装配式尼龙前胶芯 L=25.7mm	1			
170006-01-001	④	YDTE1073	M17 铆铜镀金压接式公端子 Ø1.0×19.15mm	6	630	14	
	②	YDCN0943	M17 8P 金属装配式尼龙后胶芯 L=14.3mm	1			
	①	YDCN0944	M17 8P 公头金属装配式尼龙前胶芯 L=14.3mm	1			
170007-01-001	④	YDTE1073	M17 铆铜镀金压接式公端子 Ø1.0×19.15mm	7	630	14	
	②	YDCN0940	M17 7P 金属装配式尼龙后胶芯 L=14.3mm	1			
	①	YDCN0941	M17 7P 公头金属装配式尼龙前胶芯 L=25.7mm	1			
170008-01-001	④	YDTE1073	M17 铆铜镀金压接式公端子 Ø1.0×19.15mm	8	630	14	
	②	YDCN0943	M17 8P 金属装配式尼龙后胶芯 L=14.3mm	1			
	①	YDCN0944	M17 8P 公头金属装配式尼龙前胶芯 L=14.3mm	1			
170009-01-001	④	YDTE1073	M17 铆铜镀金压接式公端子 Ø1.0×19.15mm	4	630	14	
		YDTE1072	M17 铆铜镀金压接式公端子 Ø0.6×20.5mm	5			
	②	YDCN0871	M17 9P 公头金属装配式尼龙后胶芯 L=14.85mm	1			
	①	YDCN0875	M17 9P 公头金属装配式尼龙前胶芯 L=25.7mm	1			



Shenzhen Signal Electronics co.,Ltd

DRAWN BY	DATE
CHECKED BY	DATE
CHECKED BY	DATE
APPROVED BY	DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE		M17 公头金属装配式连接器	
SGN NO	见附表	REV.	
DWG NO		SO	
CUSTOMER			
TOLERANCES ARE:		THIRD ANGLE PROJECTION	
DECIMALES	ANGLES	SIZE: A4	UNITS: mm
.x ±0.5	x.* ±2.0°	SCALE: 1:1	SHEET: 1 OF 1
.xx ±0.2	.x.* ±1.0°		